

# Heat Shrinkable Bus Bar Protection Tubing

Heat Shrinkable Bus Bar Protection Tubing is made of flame retardant, Anti-UV cross linked polyolefins, and may be used on both indoor and outdoor Copper or Aluminum bus bars.

25 kV/mm dielectric strength, results in reducing permissible clearance between bus bars.



Color  
■ RED



Range / Dimensions of the Product

| Code & Size | D min (mm) | d max (mm) | t min (mm) | Spool Length (M/spool) |
|-------------|------------|------------|------------|------------------------|
| BBM 19/6    | 19         | 6          | 2          | 30                     |
| BBM 30/12   | 30         | 12         | 2.3        | 25                     |
| BBM 50/20   | 50         | 20         | 2.5        | 15                     |
| BBM 75/30   | 75         | 30         | 2.6        | 15                     |
| BBM 100/40  | 100        | 40         | 3          | 15                     |
| BBM 120/50  | 120        | 50         | 3          | 25                     |

Range / Dimensions of the Product

| Code & Size | D min (mm) | d max (mm) | t min (mm) | Spool Length (M/spool) |
|-------------|------------|------------|------------|------------------------|
| TBMT 30/12  | 30         | 12         | 2.5        | 50                     |
| TBMT 50/20  | 50         | 20         | 2.9        | 40                     |
| TBMT 75/30  | 75         | 30         | 3.8        | 40                     |
| TBMT 100/40 | 100        | 40         | 4.0        | 25                     |
| TBMT 120/50 | 120        | 50         | 3.7        | 25                     |
| TBMT 150/60 | 150        | 60         | 4.8        | 25                     |

Range / Dimensions of the Product

| Code & Size | D min (mm) | d max (mm) | t min (mm) | Spool Length (M/spool) |
|-------------|------------|------------|------------|------------------------|
| TBHT 36/10  | 36         | 10         | 2.5        | 50                     |
| TBHT 46/14  | 46         | 14         | 2.9        | 40                     |
| TBHT 54/16  | 54         | 16         | 3.8        | 40                     |
| TBHT 66/20  | 66         | 20         | 4.0        | 25                     |
| TBHT 95/30  | 95         | 30         | 3.7        | 25                     |