


Heat Shrinkable Adhesive Lined Tubing

Heat Shrinkable Adhesive Lined Tubing is made of flame retardant, Anti-UV cross linked Polyolefins, with and/or without inner layer of hot-melt adhesive. These Tubing is suitable for electrical insulation and mechanical protection in low and medium voltage power cables and cable accessories.



Color
■ Black



Range / Dimensions of the Product

Code & Size	D min (mm)	d max (mm)	t min (mm)	Length (cm)
MWC 12/3	12	3	1.8	100
MWC 55/16	55	16	2.7	100
MWC 75/22	75	22	3	100
MWC 12/3	12	3	2.5	100
MWC 19/6	19	6	3	100
MWC 28/9	28	9	3.55	100
MWC 38/12	38	12	3.9	100
MWC 51/16	51	16	4	100
MWC 68/22	68	22	3	100
MWC 75/22	75	22	4.1	100
MWC 85/25	85	25	4.3	100
MWC 105/30	105	30	4.3	100
MWC 130/36	130	36	4.3	100
MWC 140/42	140	42	4.3	100
MWC 160/50	160	50	4.3	100
MWC 180/58	180	58	4.3	100
FSA (MPS 10) 12/3	12	3	1.6	100
FSA (MPS 10) 19/6	19	6	2.2	100
FSA (MPS 10) 30/8	30	8	2.2	100
FSA (MPS 10) 40/12	40	12	2.2	100
FSA (MPS 10) 50/16	50	16	2.5	100
FSA (MPS 10) 75/22	75	22	2.8	100
FSA (MPS 10) 115/34	115	34	3.3	100
FSA (MPS 10) 140/42	140	42	3.5	100
FSA (MPS 20) 13/4	13	4	2.3	100
FSA (MPS 20) 19/6	19	6	2.6	100
FSA (MPS 20) 33/8	33	8	3.2	100
FSA (MPS 20) 45/12	45	12	4.4	100
FSA (MPS 20) 51/16	51	16	4.3	100
FSA (MPS 20) 85/25	85	25	4.2	100
FSA (MPS 20) 105/30	105	30	4.1	100
FSA (MPS 20) 130/36	130	36	4	100
FSA (MPS 20) 165/50	165	50	4.3	100
FSA (MPS 20) 185/50	185	50	4.4	100