

# LV Heat Shrinkable Terminations

Low voltage heat shrinkable terminations may be supplied for indoor and outdoor use, in voltages below 1kV. These terminations are available in single or multi-core arrangements, equipped with copper, aluminum, or bimetallic cable lugs.

LV heat shrinkable terminations are UV resistant and anti-tracking, and available for various armored and non-armored LV cables from 1.5 up to 630 mm<sup>2</sup>.

Manufactured according to IEC 60502 Standard

Available in lengths greater than standard, as per buyer's order specifications.



Selection Table:		<b>ELCOTERM T<sup>1</sup>S 01<sup>2</sup>/<sup>3</sup>/<sup>4</sup>/<sup>5</sup></b>									
<b>1</b> Installation		<b>2</b> Armour		<b>3</b> Cable Cores		<b>4</b> Lead Sheath		<b>5</b> Cable Size			
<b>I</b>	Indoor	<b>I</b>	Non-Armoured	<b>1 C</b>	1 Core	<b>-</b>	No Lead Sheath	As Required			
				<b>2 C</b>	2 Core						
				<b>3 C</b>	3 Core						
<b>E</b>	Outdoor	<b>E</b>	Armoured	<b>3½ C</b>	3 ½ Core	<b>L</b>	Lead Sheath				
				<b>4 C</b>	4 Core						
				<b>5 C</b>	5 Core						
Example:		<b>TIS 017/4C/16</b>				Indoor LV heat shrinkable termination for 4 x 16 mm <sup>2</sup> armored cable					